

# Safety data sheet for AIREX® T90 T92

According to Regulation (EC) No. 1907/2006 & GHS

Page 1 of 3

revised: January 23<sup>rd</sup>, 2017 GM--SDS-016

### 1. Identification of substance / preparation and of the company

AIREX® T90/T92 Rigid foam

(T90.60, T90.100, T90.150, T90.210)

(T92.60, T92.80, T92.100, T92.110, T92.130, T92.200, T92.320)

Use of substance / preparation : Core material in sandwich constructions

Company identification: Airex AG

5643 Sins, Switzerland Tel +41 41 789 66 00 Fax +41 41 789 66 60

#### 2. Hazards identification

AIREX® T90/T92 does not constitute any risk to public health and environment if it is used as intended.

Fine dust is produced while sawing, milling, grinding and sanding.

Molten product adheres to the skin and causes burns.

May contain residuals from physical blowing agent (hydrocarbons).

### 3. Composition / Information on ingredients

Rigid polymeric foam on the basis of Polyethylenterephtalate.

### 4. First aid measures

Inhalation of gases in case of fire: Move victim to fresh air and obtain medical attention.

Skin contact: Molten product on the skin should be cooled rapidly with cold water, but not pulled off.

Obtain medical attention.

Eye contact: Flush with water if irritation develops.

Ingestion: No special measures required. Seek medical attention if symptoms develop.

## 5. Fire-fighting measures

Specific hazards: Not classified as flammable but will burn. Toxic gases contain carbon monoxide (CO)

and others.

Suitable extinguishing media: Foam, water spray, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used: Direct water jet.

Use respiratory protection independent of recirculated air.

### 6. Accidental release measures

No special measures required.

#### 7. Handling and storage

Handling: No special measures required. Avoid generation or accumulation of dusts. Take

precautionary measures against static discharges. Earth all equipment.

Storage: Stow away from immediate and dangerous sources of ignition. Danger of electrostatic

charges when stored in very dry areas.







## Safety data sheet for AIREX® T90 T92

According to Regulation (EC) No. 1907/2006 & GHS Page 2 of 3 revised: January 23<sup>rd</sup>, 2017

GM--SDS-016

8. Exposure control / personal protection

Exposure limit values: Not applicable.

Exposure controls: The use of gloves, protective goggles and dust masks and also the use of dust extraction

equipment is recommended for sawing, milling, grinding and sanding. For

thermoforming, the workplace should be continuously supplied with fresh air. Where

necessary, a respiratory protection is recommended.

9. Physical and chemical properties

Physical state / form: Polymer foam sheet with visible cell structure.

Colour. White

Melting temperature: 250 °C

Decomposition temperature > 340 °C

Flash ignition temperature 370 °C DIN 51794

Density: 60 - 320 kg/m³ ISO 845

Solubility: Insoluble in: Water, sea water, acids, alkalis, aliphatic hydrocarbons

Soluble in: Aromatic hydrocarbons, ketones, chlorinated hydrocarbons

10. Stability and reactivity

General information: Stable under normal conditions

Conditions to avoid: Not applicable

Materials to avoid: Oxidising agents

Dangerous decomposition products: Carbon monoxide (CO), acetaldehyde, acidic gases

11. Toxicological information

Toxicological tests: Based on MSDS of base material producer

Experience with man:

Skin contact: Does not contain any materials which are known to stimulate allergic reactions.

Grinding dust may cause irritation to people with sensitive skin.

Eye contact: Dust may cause irritation.

Inhalation: Dust may cause irritation of respiration tract.

Ingestion: Low toxicity, LD50 > 2000 mg/kg

12. Ecological information

Ecotoxicity: Not determined

Mobility: Not soluble in water, therefore effects on groundwater are unlikely

Persistence and degradability: Biologically not degradable

13. Disposal considerations

Subject to legislation by local authorities, the product can be disposed of together with domestic refuse and industrial waste. Waste and residues can be incinerated in a plant equipped with flue gas washing, together with domestic waste.

14. Transport information

Railroad RID No restriction.

Road ADR No restriction.

Sea IMDG Code No restriction.

Air ICAO-TI/IATA-DGR No restriction.

UN-Classification Not required.





## Safety data sheet for AIREX® T90 T92

According to Regulation (EC) No. 1907/2006 & GHS

Page 3 of 3

revised: January 23<sup>rd</sup>, 2017 GM--SDS-016

### 15. Regulatory information

AIREX® T90/T92 rigid plastic foam does not require marking under the following directives or is not concerned by the following regulations:

- Europe: Directive 67/548/EWG, ("DSD"), Directive 1999/45/EC, ("DPD"), Regulation (EC) No 1272/2008 ("CLP").
- US: OSHA .29 CFR 1910.1200 and .49 CFR 171.8 (EPA 40 CFR 117) spill, leak and disposal regulations of the US Department of Transportation.
- Canada: WHMIS and TDG.

#### 16. Other information

This issue of the safety data sheet replaces the issue released on July 22<sup>nd</sup>, 2016.

The information given in this material safety data sheet is accurate to the best of our knowledge, but without any guarantee. It is given in good faith based on the current state of knowledge and experience. It is issued in respect of safety requirements and does not purpose to provide information on the quality of the material.

